



CONNECTORS

## RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

### 5mm B-T-W Conn. 3P HDR ASSEMBL

AMP | Power Double Lock

1376383-1

TE Internal Number: 1376383-1

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Receptacle**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating (A) **9**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**



#### Product Drawings

[5.0 POWER KEY CONNECTOR 3P HEADER ASSEMBLY](#)

PDF  
English

#### CAD Files

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[SOFT\\_SHELL\\_PIN\\_SOCKET\\_CONNECTORS\\_STANDARD\\_DENSITY](#)

PDF  
English

#### Product Specifications

Product Specification	<a href="#">5.0 POWER KEY CONNECTOR</a> PDF <b>English</b>
Application Specification	<a href="#">5.0 POWER KEY CONNECTOR</a> PDF <b>Japanese</b>
Qualification Test Report	<a href="#">5.0 POWER KEY CONNECTOR</a> TIF <b>Japanese</b>
	<a href="#">5.0 PKC QUALIFICATION TEST REPORT</a> PDF <b>Japanese</b>
	<a href="#">5.0 PKC QUALIFICATION TEST REPORT</a> TIF <b>Japanese</b>

---

## Product Environmental Compliance

TE Material Declaration	<a href="#">MD_1376383-1_0330201523_dmtec</a> PDF <b>English</b>
-------------------------	--

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Product Type	<b>Header</b>
	Housing Type	<b>Receptacle</b>
	Contact Type	<b>Pin, Tab</b>
	Header Type	<b>Shrouded</b>

---

Configuration Features	Number of Positions	<b>3</b>
	Centerline	<b>5 mm [ .197 in ]</b>
	PCB Mounting Orientation	<b>Vertical</b>
	Number of Rows	<b>1</b>
	Contact Layout	<b>Inline</b>
	Keying	<b>A</b>

---

Electrical Characteristics	Contact Current Rating (A)	<b>9</b>
	Operating Voltage (VAC)	<b>300</b>

---

Contact Features	Contact Termination Area Plating Material	<b>Tin</b>
	Contact Mating Area Plating Material	<b>Tin</b>
	Contact Mating Area Plating Thickness	<b>1 μm [ 39.37 μin ]</b>
	Contact Base Material	<b>Copper Alloy</b>
	Contact Termination Area Plating Thickness	<b>1 μm [ 39.37 μin ]</b>

---

Termination Features	Termination Method to PC Board	<b>Through Hole - Press-Fit</b>
----------------------	--------------------------------	---------------------------------

	Termination Post/Tail Length	<b>3.5 mm [ .138 in ]</b>
Mechanical Attachment	Mating Alignment	<b>Without</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Mounting Post/Kinked Legs</b>
	PCB Mount Alignment	<b>Without</b>
	Mating Retention Type	<b>Latch</b>
Housing Features	UL Flammability Rating	<b>UL 94V-0</b>
	Housing Color	<b>Natural</b>
	Housing Material	<b>Nylon 6/6 GF</b>
Dimensions	Mating Post Length	<b>6.3 mm [ .248 in ]</b>
	Width	<b>14.1 mm [ .555 in ]</b>
	Height	<b>14.1 mm [ .55 in ]</b>
	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Length	<b>16.6 mm [ .653 in ]</b>
Usage Conditions	Sealed Condition	<b>Not Sealed</b>
Operation/Application	Connector System	<b>Wire-to-Board</b>
	Applies To	<b>Printed Circuit Board</b>
	Operating Temperature	<b>-30 – 105 °C [ -22 – 221 °F ]</b>
	Circuit Application	<b>Signal/Power</b>
Industry Standards	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	Agency/Standard Number	<b>E28476</b>
	UL Rating	<b>Recognized</b>
	CSA File Number	<b>LR7189</b>
	Agency/Standard	<b>CSA, UL</b>
Packaging Features	Packaging Method	<b>Bag</b>
	Packaging Quantity	<b>100</b>
Other	For Use With	<b>Plug Housing</b>
	Selectively Loaded	<b>No</b>

---

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

